

Skirting tape foam backing

UZIN ULTRATAC 1,3

High-performance foam adhesive tape for installing profiles and strips

PRODUCT BENEFITS/FEATURES:

- ▶ Aluminium skirting boards
- ▶ Plastic skirting boards
- ▶ Dust mouldings
- ▶ Sheathed MDF skirting boards
- ▶ Electrical ducts

SUITABLE ON / FOR:

- ▶ Smooth plaster
- ▶ Abrasion up to 1.0 mm
- ▶ Levelling compounds
- ▶ Colour coats
- ▶ Concrete
- ▶ Wood
- ▶ Metal
- ▶ Plastic / melamine resin



PRODUCT BENEFITS/FEATURES:

Double-sided adhesive system with different adhesive forces on both sides, based on a high-performance foam carrier, for the installation of skirting boards and profiles made of aluminium or plastic. For indoor use.

- ▶ Quick and easy processing
- ▶ Immediate adhesion/locking
- ▶ No visible screws
- ▶ Installation without noise / dust
- ▶ Solvent-free



TECHNICAL DATA:

Packaging	carton
Pack size	6 rolls
Shelf life	min. 24 months
Color	grey
Open time	unlimited
Working time	unlimited
Setting time / cure time	none
Roll width	20 mm
Thickness	1,3 mm
Minimum application temperature	15 ° C at ground level
Joint sealing	immediately after installation

*At 20 °C and 65% relative humidity.



for Aluminium and plastic skirting boards
ON substrates up to 1mm structure

SUBSTRATE PREPARATION:

- ▶ The substrate must be permanently dry, hard, load-bearing, flat, free from grease, dust and silicon, in accordance with the respective national standards (EN, DIN, VOB, OE, SIA).
- ▶ Acclimatise the skirting boards + profiles as well as the UZIN Ultratac 1,3 well for 24 hours at at least 16 °C in the appropriate room.
- ▶ Wallpaper must be firmly bonded or cut / removed for the height covered by the skirting.
- ▶ Bind dust with a solvent-free, film-forming primer.
- ▶ Ensure the floor covering and skirting are free from distortions before installing.
- ▶ Before installing, carry out your own adhesive tests to check the bond on the skirting board and the substrate.

APPLICATION:

- ▶ The skirting boards to be glued must first be cut to size and customised beforehand. Then dust off the gluing surfaces and clean well.
- ▶ The UZIN Ultratac 1,3 is then applied to the upper edge at the back of the skirting board.
- ▶ In the area of outside corners a second adhesive strip is also used, with a length of 10-15 cm attached at the bottom edge. This prevents unwanted movement of the finished corner.
- ▶ For skirting boards >60 mm, a second strip of UZIN Ultratac 1,3 must always be applied along the bottom edge to ensure a tight fit.
- ▶ To fit the skirting boards, the protective film is peeled off continuously and the skirting board is fitted to the wall without tension and pressed firmly into place.
- ▶ The skirting board must then be pressed or tapped into place without any gaps.

When a skirting board bonded with UZIN Ultratac 1,3 is removed at a later date, adhesive residues may remain on the substrate. Adhesive residues can only be removed mechanically.

If required, the upper connecting edge to the wall can be grouted with an acrylic joint in a matching colour.

IMPORTANT NOTES:

- ▶ Aluminium skirting with or without a base, foamed plastic skirting boards, as well as various baffle strips and electrical ducts are suitable for bonding.
- ▶ Stresses caused by uneven walls or at external corners may need to be reinforced with an assembly adhesive or hotmelt.

Storage:

Store on a protected cut surface in a dry, cool place out of direct sunlight. Repack opened rolls in the carton.

Shelf life: 24 months

SEALS OF QUALITY & ECOLABELS:

- ▶ EMICODE EC 1 PLUS / Very low emission
- ▶ Manufacturer specific EPD
- ▶ Suitable for sustainable building certifications according to: DGNB, QNG, BNB, BREEAM, LEED

COMPOSITION:

Acrylic copolymers, wetting and defoaming agents, plastic film, paper.

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

The product does not require any special labour protection measures. For reasons of working hygiene, we recommend avoiding eating, drinking and smoking during processing of this product. Store out of the reach of children. For more information refer to www.uzin.com or contact +49 731 4097-0.

DISPOSAL:

Empty shells and the cardboard packaging can be recycled. Material remnants can be disposed of as household waste.